

SNGII

Nitrogen Generators

- › **Pressure**
5000 to 6000 psig
345 to 414 bar
- › **Capacity**
4 to 25 scfm
113 to 708 l/min
- › **Power**
20 to 60 hp
15 to 45 kw



The Series II Stationary Nitrogen Generation systems are turnkey solutions designed to generate compressed, high purity nitrogen gas for a diverse range of markets such as plastics processing, industrial, and military applications.

These self-contained, fully integrated systems do not require shop air and eliminate the hazards involved with the handling of high pressure cylinders as well as the burden of merchant-supplied bulk gas. **Why buy Nitrogen when you can make your own?**

SNGII

STANDARD SCOPE OF SUPPLY

- › Feed air compressor, single-stage, air cooled, oil-injected, continuous-duty screw compressor
- › High pressure booster, multi-stage, air cooled, pressure lubricated, continuous-duty rated
- › High durability membrane air separators
- › Electric motors (ODP) two each with v-belt drive, belt guard and belt tensioning device
- › Automatic condensate drain with collector (includes switch for high condensate level)
- › **UL**[®] labeled Control Center with PLC controller. Master central system includes interactive touchscreen interface for operation, maintenance and troubleshooting.
- › Single-point power supply connection, fused control voltage transformer
- › On-line percent oxygen monitor
- › Pressure sensors for oil and final product pressure
- › Emergency stop push button
- › Visible alarm annunciation
- › Locally mounted pressure gauges
- › Sound attenuated enclosures for compressors and membrane module
- › Ambient temperature range 40° to 113° F
- › 12 month warranty

AVAILABLE ACCESSORIES

- › Portable percent oxygen monitor
- › CE-complaint electrical assembly
- › TEFC motors
- › Second language for controls / documentation

DIMENSIONS L x W x H inches (mm)

- › ≤ 30 hp, 85 x 59 x 74 (2156 x 1482 x 1867)
- › > 30 hp, 96 x 64 x 84 (2426 x 1626 x 2116)

WEIGHT pounds (kg)

- › ≤ 30 hp, 2800 (1045)
- › > 30 hp, 3800 (1418)

SOUND LEVEL (from control panel)

- › ≤ 30 hp, 70 dBA ± 2dBA
- › > 30 hp, 79 dBA ± 2dBA

Technical Data

Model	Product flow at 99.5% purity		Product flow at 99.0% purity		Product flow at 98.0% purity		Motor	
	scfm ¹⁾	l/min	scfm ¹⁾	l/min	scfm ¹⁾	l/min	hp	kw
5000 psig (345 bar)								
SNGII-15305	4	113	5.5	156	7.5	212	20	15
SNGII-20410	7	198	11	311	14	396	30	22
SNGII-30615	13	368	18	510	26	736	45	34
SNGII-40815	25	708	26	736	27	765	55	41
6000 psig (414 bar)								
SNGII-15376	10	254	10	254	10	254	22.5	17
SNGII-40820	25	708	25	708	25	708	60	45

1) Capacity (FGD) is referenced to standard conditions. Tolerance +/- 5%.
Dimensions and weight are approximate and are dependent upon model and drive.

BAUER COMPRESSORS INC.

1328 Azalea Garden Road | Norfolk, VA 23502
 TEL. +1 (757) 855-6006
 FAX +1 (757) 857-1041
sls@bauercomp.com
www.bauercomp.com

BAUER PLASTICS TECHNOLOGY GROUP

37450 Garfield Road | Clinton Township, MI 48036
 TEL. +1 (586) 286-0360
 FAX +1 (586) 286-2650
info@bauerptg.com
www.bauerptg.com